



IVN-21EIR

IP Turret Camera, 2MP, 1080P, 2.8mm lens, 2pcs Array IR, POE, waterproof RJ45

High performance CMOS image sensor, with 2MP resolution
H.264/H.265/H.265+ dual-stream
Max resolution 1920*1080
Onvif
ICR switching
IP66 Metal Turret case
2PCS Array IR Led, 20M
2.8 mm lens
PoE and DC12V 400 mA

Camera	
Image Sensor	1/2.9, 2MP CMOS GC2063
Min. Illumination	Colour 0.01 Lux
Signal to noise ratio	≥ 37 dB
Video	
Video processing	Supports automatic white balance, supports 3-DNR, dWDR, anti-face overexposure, and dehazing function, H.264/H.265/H.265+ different encoding formats are available, realize ultra-low storage, adjustable bit rate/frame rate
Audio	
Audio Port	One audio input One audio output, G711U/G711A encoding, support simplex two-way voice intercom
Network	
Network Interface	One RJ45, 10/100M adaptive Ethernet interface 2KV lightning protection meter
Protocol Support	Support HTTP/RTSP/NTP/DHCP/ONVIF/P2P lamp network protocol, optional GB28181, RTMP and multiple private NVR protocols
Intelligent Functions	IE6.0 and above (Web Server embedded in the device) browser use Motion detection and OSD customization P2P cloud service Support mobile web access Support IP filtering
Image	
Image Resolution	<i>Main stream:</i> 1080P(default)/720P/D1@30fps <i>Sub stream:</i> D1/VGA/640*360/CIF@30fps
General	
Mobile client	Support Windows Mobile, iPhone, iPad, Android
Business functions	Support IE6.0 and above (device embedded Web Server) browser browsing, support front-end storage playback/download, support unified client software, Support CMS platform system application, provide SDK development kit
Work Environment	-30 °C ÷ ~85 °C
Camera Dimension	106.61 (D) x 81.78 (H) mm