



## IWN-21EVR

IP Bullet Camera 2 MP, 2.8-12 mm lens, 5 pcs array IR, Colour: 0.1 Lux/(F1.2), Dual stream, 1 ch audio in/out, Hardware reset, Onvif 2.4, P2P, IP66.

High performance CMOS image sensor, with 2 MP resolution

H.264/H.265/H.265+, dual-stream

Resolution 1920\*1080

Onvif

ICR switching

IP66 metal bullet casing

5 pcs Array IR LED, 40 m

2.8 ~ 12 mm lens

Power supply: PoE/12 Vdc 550 mA

1 CH AUDIO I/O, Support hardware reset

Camera	
Image Sensor	1/2.9, 2MP CMOS GC2063
Min. Illumination	Colour 0.01 Lux
Signal to noise ratio	≥ 37 dB
Video	
Video processing	Supports automatic white balance, supports 3-DNR, dWDR, anti-face overexposure, and dehazing function, H.264/H.265/H.265+ different encoding formats are available, realize ultra-low storage, adjustable bit rate/frame rate.
Audio	
Audio Port	One audio input One audio output, G711U/G711A encoding, support simplex two-way voice intercom
Network	
Network Interface	One RJ45, 10/100M adaptive Ethernet interface 2KV lightning protection meter
Protocol Support	Support HTTP/RTSP/NTP/DHCP/ONVIF/P2P lamp network protocol, optional GB28181, RTMP and multiple private NVR protocols
Intelligent Functions	IE6.0 and above (Web Server embedded in the device) browser use Motion detection and OSD customization
	IE6.0 and above (Web Server embedded in the device) browser use Motion detection and OSD customization
	P2P cloud service
	Support mobile web access
Image	
Image Resolution	Main stream:
	1080P (default)/720P/D1@30fps
	Sub stream:
General	
Mobile client	Support Windows Mobile, iPhone, iPad, Android
Business functions	Support IE6.0 and above (device embedded Web Server) browser browsing, support front-end storage playback/download, support unified client software, Support CMS platform system application, provide SDK development kit
Work Environment	-30 °C ÷ +85 °C
Camera Dimension	295.1 x 78.6 mm