

TWN-24IRL

4 in 1 HD TVI BULLET



KEY FEATURES

- High performance CMOS image sensor, with 2.0 mega-pixel resolution
- Coaxial transmission for HD video and control signal
- Common 75-5 similar coaxial cables lossless transmission up to 300 meters
- High speed, long distance, real-time transmission
- ICR switching
- TVI/AHD/CVI/ CVBS signal output (switch cable)
- IP66 bullet case
- 18pcs SMD LED, up to 20 meter
- 3.6mm lens



SPECIFICATION	TWN-24IRL
Pick Up Element	1/3"CMOS 2 Mega Pixels
Number of Pixels	1920(H)×1080(V)
Horizontal Resolution	1080P
IR Function	Yes (Built-in IR CUT filter)
Video frame rate	1920×1080@25fps
Minimum Illumination	0.01Lux(F1.2)
Electronic Shutter	1/50s-1/10000s
IR LED	18pcs SMD LED, up to 20 meter
Video output	TVI (default) / CVI / AHD/ CVBS
OSD	Entered through TVI recorder
Language	English
WDR	dWDR OFF/ON
DNR	2D-DNR
WHITE Balance	ATW/MWB
AE MODE	GLOBE/BLC
Day/Night	Ext Color, B/W
Transmission distance	75-5 300M
Coaxial	Yes
Power/Current	12VDC(±10%)/ 450mA
Lens	3.6 mm
Water Resistance	IP66
Storage Temperature	-30~ +60°C RH95% Max
Operating Temperature	-20~ +50°C RH95% Max
Case Dimension	151,16(L)×65,55(W)×64,1(H) mm



DIMENSIONS

