

TWN-44IRL

4 in 1 HD TVI BULLET



KEY FEATURES

- High performance CMOS image sensor,with 4.0 mega-pixel resolution
- Coaxial transmission for HD video and control signal
- Common 75-5 similar coaxial cables lossless transmission up to 300 meters
- High speed,long distance,real-time transmission
- ICR switching
- TVI/AHD/CVI/CVBS singnal output (switch cable)
- IP66 bullet case
- 18pcs SMD LED, up to 20 meter
- 3.6mm lens



| SPECIFICATION | TWN-44IRL |
|-----------------------|------------------------------------|
| Pick Up Element | 1/3"CMOS 4 Mega Pixels |
| Active Pixel | 2560*1440 |
| SYNC. | Internal |
| Resolution | 4MP(25fps) 1080P |
| VIDEO.OUT | AHD/CVI/TVI/CVBS |
| Lens | 3.6mm |
| IR Series Distance | Max.20 Meter with 18pcs SMD IR LED |
| Power supply | DC12V,450mA |
| Minimum Illumination | 0.01Lux(F1.2) |
| Electric Shutter | 1/25s-1/10000s |
| S/N Ratio | 48dB(min)(AGC closed) |
| MIRROR | DEFAULT/H/V/HV |
| WDR | d-WDR |
| DNR | 2D-DNR 1-10 |
| WHITE Balance | ATW/MWB |
| AE MODE | GLOBE/BLC |
| OSD | Yes(optional) |
| Coaxial | Yes |
| Language | English, Italian, Spanish |
| Day/Night | Ext Color, B/W |
| Transmission distance | 75-5 300M |
| Operation Temperature | -20~ +50°C RH95% Max |
| Case Dimension | 151,16(L)×65,55(W)×64,1(H) mm |



DIMENSIONS:

