



## IVN-22EVR

IP Turret Camera 2 MP,1080P, 2.8~12 mm lens, 3 pcs array IR, PoE, hardware reset, audio I/O, IP66 metal case

High performance CMOS image sensor, with 2 MP resolution

H.264/H.265/H.265+, dual stream

Resolution 2304x1296, default 1920x1080

Onvif

True WDR, 3D-DNR

ICR switching

2.8~12 mm lens

3 pcs Array IR LED, Max, 30 m

IP66 metal Turret case

12 Vdc/PoE, 500 mA

1 ch audio I/O, Support hardware reset

### Camera

DSP	Mstar335
Image Sensor	1/2.8 SONY SENSOR IMX307
Min. Illumination	Colour 0.01 Lux
Signal to noise ratio	≥ 50 dB

### Video

Video processing	Supports automatic white balance, supports 3D-DNR, true WDR, anti-face overexposure, and dehazing function, H.264/H.265/H.265+ different encoding formats are available, realize ultra-low storage, adjustable bit rate/frame
------------------	---

### Audio

Audio Port	One audio input One audio output, G711U/G711A encoding, support simplex two-way voice intercom
------------	--

### Network

Network Interface	One RJ45, 10/100 M adaptive Ethernet interface 2 KV lightning protection meter
Protocol Support	Support HTTP/RTSP/NTP/DHCP/ONVIF/P2P lamp network protocol, optional GB28181, RTMP and multiple private NVR protocols IE6.0 and above (Web Server embedded in the device) browser use Motion detection and OSD customization
Intelligent Functions	Humanoid detection P2P cloud service Support mobile web access Support IP filtering

### Image

Image Resolution	<i>Main stream:</i> 1080P (default)/720P/D1 @30fps <i>Sub stream:</i> D1/VGA/640x360/CIF @30fps
------------------	--

### General

Mobile client	Support Windows Mobile, iPhone, iPad, Android
Supported software	<i>Plug-in required live view:</i> IE 10, IE 11 <i>Plug-in free live view:</i> Chrome, Firefox, Edge (device embedded Web Server) browser browsing, support front-end storage playback/download, support unified client software, Support CMS platform system application, provide SDK development kit
Work Environment	-30 °C ÷ +85 °C
Camera Dimension	145 (D) x 107.86 (H) mm