

Item code: 70314-TWH-51LIX

Product description: HD-TVI Bullet Camera VALUE Series

Main features: 5 MP High-performance CMOS, Outdoor EXIR, ICR, Colour: 0.01 Lux/(F1.2, AGC ON), 0 Lux with IR, 2D-DNR, IP67, Metal & Plastic.



SPECIFICATIONS

Camera	
Image Sensor	5 MP CMOS
Signal System	PAL/NTSC
Resolution	2560 (H) × 1944 (V)
Frame Rate	TVI: 5 M@20fps, 4 M@30fps, 4 M@25fps, 1080p@30fps, 1080p@25fps AHD: 5 M@20fps, 4 M@30fps, 4 M@25fps CVI: 4 M@30fps, 4 M@25fps CVBS: PAL/NTSC
Min. illumination	0.01 Lux@(F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 ÷ 1/50,000 s NTSC: 1/30 ÷ 1/50,000 s
Lens	2.8 mm fixed lens
Field of View	Horizontal FOV: 85° Vertical FOV: 63° Diagonal FOV: 110°
Lens Mount	M12
Day & Night	ICR
WDR (Wide Dynamic Range)	Digital WDR
Angle Adjustment	Pan: 0° ÷ 360° Tilt: 0° ÷ 75° Rotation: 0° ÷ 360°
Menu	
Image Mode	STD/HIGH-SAT
AGC	Yes
Day/Night Mode	Auto/Colour/BW (Black and White)
White Balance	Auto/Manual
AE (Auto Exposure) Mode	DWDR/BLC/HLC/Global
Noise Reduction	2D-DNR
Language	English
Function	Brightness, Sharpness, Mirror, Smart IR
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS

General	
Operating Conditions	-40 °C ÷ 60 °C (-40 °F ÷ 140 °F); humidity: 90% or less (non-condensation)
Power Supply	12 Vdc ± 25%
Power Consumption	Max 4.3 W
Protection Level	IP67
Material	Metal
IR Range	Up to 30 m
Dimensions	60.9 × 57.9 × 138.8 mm (2.39" × 2.28" × 5.47")
Weight	~258 g (0.35 lb)



BS OHSAS 18001: 2007
Occupational Health and
Safety Management System



ISO 9001: 2015
Quality Management
System



ISO 14001: 2015
Environmental Management
System



CI ITPI: 2015
100% Made in Italy
Certificate



MAZi – Brand distributed by LINCE ITALIA S.p.A.
Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia
Tel.: +39 06 92928252 - Fax: +39 06 92942586
www.lince.net – info@lince.net
MD-03.11 Rev. 6 - Pag.: 2 di 2