

Item code: 70448-TWH-23LIX

Product description: HD-TVI Bullet Camera VALUE Series 2 MP

Main features: 2 MP High-performance CMOS, EXIR 2.0, Colour: 0.01 Lux/(F1.2, AGC ON), 0 Lux with IR, DNR, IP66, Metal & Plastic.


SPECIFICATIONS

Camera	
Image Sensor	2 MP CMOS
Signal System	PAL/NTSC
Frame Rate	TVI: 1080 P@30 fps, 1080 P@25 fps CVI: 1080 P@30 fps, 1080 P@25 fps AHD: 1080 P@30 fps, 1080 P@25 fps CVBS: PAL/NTSC
Resolution	1920 (H) × 1080 (V)
Min. illumination	0.01 Lux@(F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 ÷ 1/50,000 s NTSC: 1/30 ÷ 1/50,000 s
Lens	3.6 mm fixed lens
Horizontal Field of View	<i>Horizontal FOV: 79.6° Vertical FOV: 43.5° Diagonal FOV: 93.7°</i>
Lens Mount	M12
Day & Night	ICR
WDR (Wide Dynamic Range)	Digital WDR
Angle Adjustment	Pan: 0 ÷ 360°, Tilt: 0 ÷ 180°, Rotation: 0 ÷ 360°
Menu	
Image Mode	STD/HIGH-SAT
AGC	Yes
Day/Night Mode	Auto/Colour/BW (Black and White)
White Balance	Auto/Manual
AE (Auto Exposure) Mode	DWDR/BLC/HLC/Global
Language	English
Functions	Brightness, Sharpness, Smart IR
2D-DNR	Yes
Interface	
Video Output	Switchable TVI/AHD/CCI/CVBS
General	
Operating Conditions	-40 °C ÷ 60 °C (-40 °F ÷ 140 °F); humidity: 90% or less (non-condensation)

Power Supply	12 Vdc \pm 25%
Power Consumption	Max 3.9 W
Protection Level	IP67
Material	<i>Front cover:</i> Metal <i>Main body:</i> Plastic
IR Range	Up to 40 m
Communication	Protocol: MAZi (TVI output)
Dimensions	78.9 mm \times 74.5 mm \times 216.6 mm (3.10" \times 2.97" \times 8.53")
Weight	\sim 320 g (0.71 lb.)



BS OHSAS 18001: 2007
Occupational Health and
Safety Management System



ISO 9001: 2015
Quality Management
System



ISO 14001: 2015
Environmental Management
System



CI ITPI: 2015
100% Made in Italy
Certificate



MAZi – Brand distributed by LINCE ITALIA S.p.A.
Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia
Tel.: +39 06 92928252 - Fax: +39 06 92942586
www.lince.net - info@lince.net
MD-03.11 Rev. 6 - Pag.: 2 di 2