

TWN-83IR

4 in 1 HD TVI BULLET



KEY FEATURES

- High performance CMOS, 8M
- 3.6mm lens
- Coaxial transmission for HD video and control signal
- Common 75-5 coaxial cables lossless transmission up to 300 meters
- High speed, long distance, real-time transmission
- ICR, dWDR, 3DNR, AGC, AWB, BLC, OSD
- TVI (default) / CVI / AHD/ CVBS output
- Cable OSD
- 3pcs array IR, 30 meter
- IP66



SPECIFICATION	TWN-83IR
Pick Up Element	1/2.3" CMOS 8 Mega Pixels
Number of Pixels	3840(H)×2160(V)
Synchronisation	Internal
Resolution	8M
Video output	TVI:8M@15fps,1080P@25fps,4MP@25fps,5MP@20fps AHD:8M@15fps,1080P@25fps,4MP@25fps,5MP@20fp CVI:8M@15fps,1080P@25fps,4MP@25fps,5MP@20fps CVBS:PAL
Lens	3.6mm
IR Series Distance	Max. 30 Meter with 3pcs IR Array
Minimum Illumination	0.01LUX(F1.2)
S/N Ratio	48dB(min)(AGC closed)
AE	GLOBE/BLC
WDR	dWDR
AWB	ATW/MWB
DNR	1-10
OSD	Yes
Language	English
Day/Night	SMART,B/W,COLOR
Power	DC12V, 600mA
Transmission distance	75-5 300M
Operation Temperature	-20°C+55°C, Humidity less than 85%RH
Case Dimension	210.5(L)×63.09(H)mm



DIMENSIONS

