

## HXVR-08P104H1



### Key Features

- | Deep learning-based motion detection 2.0 for all analog channels
- | Deep learning-based perimeter protection
- | H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 video compression
- | HDTV/AHD/CVI/CVBS/IP video inputs
- | Audio via coaxial cable
- | Up to 16-ch IP camera inputs (up to 8 MP)
- | Up to 10 TB capacity per HDD

### Compression and Recording

- | H.265 Pro+ can be enabled to improve encoding efficiency and reduce data storage costs
- | Recording at up to 8 MP resolution

### Storage and Playback

- | Smart search for efficient playback
- | Support the third-party cloud storage

### Smart Function

- | Deep learning-based motion detection, and perimeter protection (line crossing and intrusion detection)
- | Support multiple VCA (Video Content Analytics) events for both analog and smart IP cameras

### Network & Ethernet Access

- | Compatible with major Wi-Fi dongle products in the market
- | CTR-MAZi & DDNS (Dynamic Domain Name System) for easy network management
- | Output bandwidth limit configurable

Model		HXVR-08P104H1
Motion Detection 2.0	Human/Vehicle Analysis	<p>Deep learning-based motion detection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leaves and lights;</p> <p>Quick search by object or event type is supported;</p>
Perimeter Protection <sup>1</sup>	Human/Vehicle Analysis	Up to 4-ch
Recording	Video compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
	Encoding resolution	<p><u>Main stream:</u>            8 MP@8 fps/5 MP@12 fps/3K@12 fps/ 4 MP@15 fps/3 MP@18 fps            1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N)</p> <p><u>Sub-stream:</u>            WD1/4CIF/CIF@25 fps (P)/30 fps (N)</p> <p><i>8 MP @8 fps is only available for channel 1.</i></p>
	Video bit rate	32 kbps to 10 Mbps
	Dual stream	Support
	Stream type	Video, Video & Audio
	Audio compression	G.711u
	Audio bit rate	64 kbps
	Video and Audio	IP video input <sup>2</sup>
Analog video input		4-ch BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection
HDTV input		8 MP@15 fps, 5 MP@20 fps, 3K@20 fps, 4 MP@30 fps, 4 MP@25 fps, 3 MP@18 fps, 1080p@30 fps, 1080p@25 fps, 720p@60 fps, 720p@50 fps, 720p@30 fps, 720p@25 fps
AHD input		5 MP@20 fps, 4 MP@25 fps, 4 MP@30 fps, 1080p@25 fps, 1080p@30 fps, 720p@25 fps, 720p@30 fps
HDCVI input		5 MP@20 fps, 4 MP@25 fps, 4 MP@30 fps, 1080p@25 fps, 1080p@30 fps, 720p@25 fps, 720p@30 fps
CVBS input		PAL/NTSC
CVBS output		1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480
VGA output		1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz
HDMI output		1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz
Video output mode		HDMI/VGA simultaneous output
Audio input <sup>3</sup>		1-ch (up to 8-ch is optional), RCA (2.0 Vp-p, 1 kΩ) 8-ch via coaxial cable
Audio output		1-ch, RCA (Linear, 1 kΩ)
Two-way audio		1-ch, RCA (2.0 Vp-p, 1 kΩ) (using the audio input)
Synchronous playback		8-ch
Network		Remote connections
	Network protocols	TCP/IP, PPPoE, DHCP, CTR-MAZi, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF
	Network interface	1, RJ45 10/100/1000 Mbps self-adaptive Ethernet interface
	Wi-Fi	Connectable to Wi-Fi network by Wi-Fi dongle through USB interface
Auxilliary Interface	SATA	1 SATA interface

	Capacity	Up to 10 TB capacity for each disk
	Serial interface	RS-485 (half-duplex)
	USB interface	<i>Front panel:</i> 1 × USB 2.0 <i>Rear panel:</i> 1 × USB 3.0
	Alarm in/out	N/A (optional to support)
General	Power supply	12 Vdc, 2 A
	Consumption (without HDD)	≤ 15 W
	Working temperature	-10 °C ÷ +55 °C (14 °F ÷ 131 °F)
	Working humidity	10% ÷ 90%
	Dimension (W × D × H)	315 × 242 × 44 mm (12.4 × 9.5 × 1.8 inch)
	Weight (without HDD)	≤ 2 kg (4.4 lb)

**Note:**

1: Motion detection 2.0 and perimeter protection cannot be enabled at the same time. Enable one function will make the other one unavailable.

2: Enhanced IP mode might be conflicted with smart events (face picture comparison, motion detection 2.0 and perimeter protection) or other functions, please refer to the user manual for details.

3: The number of audio inputs and alarm in/out can be optional. The tag on the package will describe audio input and alarm in/out parameters. For example, "4A+8/4ALM" means your device has 4 audio inputs, 8 alarm inputs and 4 alarm outputs. If your device only has 1 audio input, the tag may not describe it.