

**Item code:** 70411-HXVR-08E101H1

**Product description:** Turbo HD DVR EASY Series

**Main features:** Turbo HD DVR 8 channels, support H.264+/H.264 video compression. HDTV input: 2 MP, AHD input: 2 MP, HDCVI input: 2 MP, CVBS input: PAL/NTSC, Audio in/out: 1/1, Serial interface: RS-485 (half-duplex), USB interface: 2 × USB 2.0, Power supply: 12 Vdc, 1.6 A.



### SPECIFICATIONS

Recording	
<b>Video compression</b>	H.264+/H.264
<b>Encoding resolution</b>	<ul style="list-style-type: none"> <li>When 1080p lite mode not enabled: 720p/WD1/4CIF/VGA/CIF</li> <li>When 1080p lite mode enabled: 1080p lite/HD 720p lite/WD1/4CIF/VGA/CIF</li> </ul>
<b>Frame rate</b>	<p><b>Main stream:</b>  <i>When 1080p lite mode enabled</i>            1080p lite/HD 720p lite/WD1/4CIF/VGA@12fps; CIF@25fps (P)/30fps (N)  <i>When 1080p lite mode not enabled</i>            For 720p stream access:            720p/WD1/4CIF/VGA@12fps; CIF@25fps (P)/30fps (N)            For SD stream access:            WD1/4CIF/VGA/CIF@25fps (P)/30fps (N)</p> <p><b>Sub-stream:</b>            CIF/QVGA/QCIF@25fps (P)/30fps (N)</p>
<b>Video bit rate</b>	32 Kbps to 4 Mbps
<b>Dual stream</b>	Support
<b>Stream type</b>	Video, Video & Audio
<b>Audio compression</b>	G.711u
<b>Audio bit rate</b>	64 Kbps
Video and Audio	
<b>IP video input</b>	Up to 8-ch Up to 960p resolution Support H.264+/H.264 IP cameras
<b>Analog video input</b>	8-ch BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection
<b>Turbo HD input</b>	1080p25, 1080p30, 720p25, 720p30
<b>AHD input</b>	1080p25, 1080p30, 720p25, 720p30
<b>HDCVI input</b>	1080p25, 1080p30, 720p25, 720p30
<b>CVBS input</b>	Support
<b>HDMI/VGA output</b>	1-ch, 1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
<b>Audio input</b>	1-ch, RCA (2.0 Vp-p, 1 KΩ)
<b>Audio output</b>	1-ch, RCA (Linear, 1 KΩ)
<b>Two-way audio</b>	Reuse the first audio input



**BS OHSAS 18001:2007**  
 Occupational Health and  
 Safety Management System



**ISO 9001:2015**  
 Quality Management  
 System



**ISO 14001:2015**  
 Environmental Management  
 System



**CI ITPI: 2015**  
 100% Made in Italy  
 Certificate



**MAZi – Brand distributed by LINCE ITALIA S.p.A.**  
 Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia  
 Tel.: +39 06 92928252 - Fax: +39 06 92942586  
[www.lince.net](http://www.lince.net) - [info@lince.net](mailto:info@lince.net)  
**MD-03.11 Rev. 6 - Pag.: 1 di 2**

<b>Synchronous playback</b>	8-ch
<b>Network</b>	
<b>Remote connections</b>	128
<b>Network protocols</b>	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS
<b>Network interface</b>	1, RJ45 10M/100M self-adaptive Ethernet interface
<b>Auxiliary Interface</b>	
<b>SATA</b>	1 SATA interface
<b>Capacity</b>	Up to 6 TB capacity for each disk
<b>Alarm in/out</b>	N/A
<b>USB interface</b>	Rear panel: 2 × USB 2.0
<b>General</b>	
<b>Power supply</b>	12 Vdc
<b>Consumption (without HDD)</b>	≤ 12 W
<b>Working temperature</b>	-10 °C ÷ 55 °C (14 °F ÷ 31 °F)
<b>Working humidity</b>	10% ÷ 90%
<b>Dimensions (W × D × H)</b>	200 × 200 × 45 mm (7.9 × 7.9 × 1.8 inch)
<b>Weight (without HDD)</b>	≤ 0.8 kg (1.8 lb)



**BS OHSAS 18001: 2007**  
Occupational Health and  
Safety Management System



**ISO 14001: 2015**  
Environmental Management  
System



**ISO 9001: 2015**  
Quality Management  
System



**CI ITPI: 2015**  
100% Made in Italy  
Certificate



**MAZi – Brand distributed by LINCE ITALIA S.p.A.**  
Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia  
Tel.: +39 06 92928252 - Fax: +39 06 92942586  
[www.lince.net](http://www.lince.net) – [info@lince.net](mailto:info@lince.net)  
**MD-03.11 Rev. 6 - Pag.: 2 di 2**