

Item code: 70341-INVR-04L108H1

Product description: NVR VALUE Series

Main features: NVR 4 Channel. Support H.265/H.265+/H.264/H.264+/MPEG4;
 Incoming bandwidth: 40 Mbps, Outgoing bandwidth: 80 Mbps; USB interface: 2 x USB 2.0, Serial Interface: RJ-45 10/100/1000 Mbps, Power supply: 12 Vdc.



SPECIFICATIONS

Video/Audio input	
IP video input	4-ch Up to 8 MP resolution
Two-way audio	1-ch, RCA (2.0 Vp-p, 1 kΩ)
Network	
Incoming bandwidth	40 Mbps
Outgoing bandwidth	80 Mbps
Video/Audio Output	
VGA Output resolution	1-ch, 1920 × 1080 p/60 Hz, 1600 × 1200/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz; HDMI/VGA simultaneous output
HDMI Output resolution	1-ch, 4K (3840 × 2160)/30 Hz, 1920 × 1080 p/60 Hz, 1600 × 1200/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz; HDMI/VGA simultaneous output
Recording resolution	8 MP/6 MP/5 MP/4 MP/3 MP/1080 p/UXGA/720 p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Audio Output	1-ch, RCA (Linear, 1 kΩ)
Decoding	
Decoding format	H.265/H.265+/H.264/H.264+/MPEG4
Live view/Playback resolution	8 MP/6 MP/5 MP/4 MP/3 MP/1080 p/UXGA/720 p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous playback	4-ch
Capability	1-ch@8 MP/4-ch@1080 p
Network Management	
Network Protocols	TCP/IP, DHCP, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS
Hard Disk	
SATA	1 SATA interface
Capacity	Up to 6 TB capacity for each disk
External Interface	
Network Interface	1, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
USB Interface	2 × USB 2.0
General	
Power supply	12 Vdc
Power	≤ 18 W
Consumption (without HDD)	≤ 10 W



BS OHSAS 18001: 2007
Occupational Health and Safety Management System



ISO 9001: 2015
Quality Management System



ISO 14001: 2015
Environmental Management System



CI ITPI: 2015
100% Made in Italy Certificate



MAZi – Brand distributed by **LINCE ITALIA S.p.A.**
 Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia
 Tel.: +39 06 92928252 - Fax: +39 06 92942586
www.lince.net – info@lince.net
MD-03.11 Rev. 6 - Pag.: 1 di 2

Working temperature	-10 °C ÷ +55 °C (14 °F to 131 °F)
Working humidity	10% ÷ 90%
Chassis	1U chassis
Dimension (W × D × H)	315 × 240 × 48 mm (12.4" × 9.4" × 1.9")
Weight (without HDD)	≤ 1 kg (2.2 lb)



BS OHSAS 18001: 2007
Occupational Health and
Safety Management System



ISO 9001: 2015
Quality Management
System



ISO 14001: 2015
Environmental Management
System



CI ITPI: 2015
100% Made in Italy
Certificate



MAZi – Brand distributed by LINCE ITALIA S.p.A.
Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia
Tel.: +39 06 92928252 - Fax: +39 06 92942586
www.lince.net – info@lince.net
MD-03.11 Rev. 6 - Pag.: 2 di 2