

Item code: 70345-INVR-04E2004H1

Product description: NVR EASY Series

Main features: NVR 4 Channel: Support H.265/H.265+/H.264/H.264+/MPEG4;
 Incoming bandwidth: 40 Mbps, Outgoing bandwidth: 80 Mbps; USB interface: 2 x
 USB 2.0, Serial Interface: RJ-45 10/100 Mbps, Power supply: 12 Vdc.



SPECIFICATIONS

Video and Audio	
IP video input	4-ch Up to 6 MP resolution
Incoming bandwidth	40 Mbps
Outgoing bandwidth	60 Mbps
HDMI output	1-ch, 1920 × 1080 p/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
VGA output	1-ch, 1920 × 1080 p/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz, HDMI/VGA simultaneous output
Decoding	
Decoding format	H.265+/H.265/ H.264+/H.264
Recording resolution	6 MP/4 MP/3 MP/1080 p/UXGA/720 p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous playback	4-ch
Capability	4-ch@1080p (25 fps), 1-ch@6 MP (25 fps)
Stream type	Video, Video & Audio
Network	
Remote connection	16
Network protocol	TCP/IP, DHCP, DNS, DDNS, NTP, SADP, SMTP, UPnP™
Network interface	1, RJ-45 10/100 Mbps self-adaptive Ethernet interface
PoE	
Interface	4, RJ-45 10/100 Mbps self-adaptive Ethernet interface
Power	≤ 36 W
Supported standard	IEEE 802.3 af/at

Auxiliary Interface	
SATA	1 SATA interface
Capacity	Up to 6 TB capacity for each disk
Alarm in/out	N/A
USB interface	Rear panel: 2 × USB 2.0
General	
Power supply	48 Vdc, 1 A
Consumption (without HDD and PoE off)	≤ 10 W
Working temperature	-10 °C ÷ +55 °C (14 °F ÷ 131 °F)
Working humidity	10% ÷ 90%
Dimension (W × D × H)	200 × 200 × 48 mm (7.9" × 7.9" × 1.9")
Weight (without HDD)	≤ 1 kg (2.2 lb)



BS OHSAS 18001: 2007
Occupational Health and
Safety Management System



ISO 9001: 2015
Quality Management
System



ISO 14001: 2015
Environmental Management
System



CI ITPI: 2015
100% Made in Italy
Certificate

