



TVN-23EIR

2 MP HD Turret Camera, 2.8 mm lens, 3 pcs array IR, IP66

2.8 mm lens

Max resolution: 1920x1080

18 pcs SMD LED, 20 m IR Range

IP66 Metal Turret

support ICR

with switching cable, can switch to different mode (AHD/TVI/CVI/CVBS)

high performance CMOS image sensor, with 2.0 mega-pixel resolution support common 75-5 similar coaxial cables lossless transmission up to 300 m above

Camera

Sensor	GC2083 1/2.9
DSP	FH8536H
Active Pixel	1920 x 1080
Minimum Illumination	0.01 Lux @(F1.2)
Resolution	2 MP
Signal to noise ratio	48 dB min (AGC closed)
Transmission distance	75-5 300 m

Video

Video out	TVI: 1080P @25/30 fps, 720P @25/30 fps AHD: 1080P @25/30 fps, 720P @25/30 fps CVI: 1080P @25/30 fps, 720P @25/30 fps CVBS: 960H
-----------	--

Network

Exposure Mode	GLOBAL/CENTER/BLC/FLC
AWB	GRAY WORLD/ATW/MWB
Day/Night	Ext/Auto/Colour/B/W
Smart LED	Auto/Manual/Close
3D-DNR/2D-DNR	Auto/Manual (0-10)
Contrast/Sharpness	Auto/Manual (0-10)
D-WDR	Close/Open
Mirror/Flip	Close/Open
OSD	Yes
Language	Eng, Chin1, Chin2, Pycc, Espanol, Francais, Polski, Japanese, Korean, Italiano, Portuges, E^HN
Day/Night	Auto, Colour, B/W, Ext

General

Power Input	12 Vdc \pm 1 V
Power Dissipation	300 mA
Operation Temperature	-10 $^{\circ}$ C \div +55 $^{\circ}$ C; Humidity less than 85% RH
Dimension (D x H)	105.98 x 63.28 mm

