

Item code: 70229-INVR-16L508H2

Product description: NVR VALUE Series

Main features: Embedded 4K NVR 16 Channel. Support H.265/H.265+/H.264/H.264+/MPEG4; Incoming bandwidth 160 Mbps, Outgoing bandwidth 160 Mbps. USB interface Front panel: 1 × USB 2.0, Rear panel: 1 × USB 3.0; Serial Interface: RJ-45 10/100 Mbps. Power supply: 12 Vdc.



SPECIFICATIONS

Video/Audio input	
IP video input	8-ch
Incoming bandwidth	80 Mbps
Outgoing bandwidth	160 Mbps
Video/Audio output	
HDMI output resolution	4K (3840 × 2160)/30 Hz, 2K (2560 × 1440)/60 Hz, 1920 × 1080/60 Hz, 1600 × 1200/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
VGA output resolution	1920 × 1080/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
Audio output	1-ch, RCA (Linear, 1 KΩ)
Decoding	
Decoding format	H.265/H.265+/H.264/H.264+/MPEG4
Recording Resolution	8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous playback	8-ch
Capability	2-ch @ 8 MP (25fps)/4-ch @ 4 MP (30fps)/8-ch @ 1080p (30fps)
Network management	
Network protocols	TCP/IP, DHCP, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP, HTTPS
Hard disk	
SATA	2 SATA interfaces
Capacity	Up to 6 TB capacity for each HDD
External interface	
Network interface	1, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
Two-way audio	1-ch, RCA (2.0 Vp-p, 1kΩ)
USB interface	Front panel: 1 × USB 2.0; Rear panel: 1 × USB 3.0
Alarm in/out	4/1
General	
Power supply	12 Vdc
Power	≤ 40 W
Consumption (without HDD)	≤ 15 W
Working temperature	-10 °C ÷ 55 °C (14 °F ÷ 131 °F)
Working humidity	10% ÷ 90%



BS OHSAS 18001:2007
Occupational Health and Safety Management System



ISO 9001:2015
Quality Management System



ISO 14001:2015
Environmental Management System




CI ITP: 2015
100% Made in Italy Certificate



MAZi – Brand distributed by **LINCE ITALIA S.p.A.**
 Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia
 Tel.: +39 06 92928252 - Fax: +39 06 92942586
www.lince.net – info@lince.net
MD-03.11 Rev. 6 - Pag.: 1 di 2

Dimensions (W x D x H)	385 x 315 x 52 mm (15.2 x 12.4 x 2.0 inch)
Weight (without HDD)	≤ 1 kg (2.2 lb)

Physical Interfaces



Index	Description	Index	Description
1	Audio IN	6	LAN Network interface
2	Audio OUT	7	USB 3.0 interface
3	VGA interface	8	GND
4	HDMI interface	9	12 Vdc power supply
5	Controller Port, Alarm In/Alarm Out	10	Power Switch