



IVN-45EVR

4 MP IP Turret Camera, 2.8-12 mm lens, IR range 30 m, PoE, IP67

1/2.9" CMOS sensor

Support H.264/H.265/H.265+ video compression standard, dual-stream

Max resolution: 2592 x 1944 @ 25fps

Support Onvif and P2P

Support ICR switching

3 pcs array LEDs, Max 30 m

2.8-12 mm lens

IP67 metal Turret/dark grey colour

support Audio I/O with hardware reset

Power supply: 12 Vdc/PoE, 500 mA

Camera

Sensor	1/2.9" 4 MP CMOS GC4653
DSP	SSC377D
Active Pixel	2592 x 1944
Minimum Illumination	Colour 0.01 Lux
Resolution	4 MP
Signal to noise ratio	≥ 50 dB min
Humanoid detection	Support

Video

Video processing	H.264/H.265/H.265+ different encoding formats are available, support stream 0.1-8 Mbps adjustable, 1-25 fps frame rate adjustable. <i>Main stream:</i> 25 fps@ (2592 x 1944); 30 fps@ (2560x1440, 2304x1296, 1080P, 720P, 1920 x 1920, 1200 x 1200)
Image Resolution	<i>Sub stream:</i> 30fps@ (D1, VGA, 640x360, 480x360, GIF, 480x480) Support CBR/VBR

Network

audio port	One audio input One audio output, G711U/G711A encoding, support simplex two-way voice intercom
Network Interface	One RJ45, 10/100 M adaptive Ethernet interface 2 KV lightning protection
Protocol support	Support HTTP/RTSP/NTP/DHCP/ONVIF/P2P lamp network protocol, RTMP and multiple private NVR protocols
Mobile client	Support Windows Mobile, iPhone, iPad, Android

General

Operation Temperature	-30 °C ÷ +85 °C
Dimension (DxH)	120 x 96.1 mm

