



IVN-81EAR

8 MP IP Motorized Turret Camera, 2.8~12 mm lens, IR range 40 m, dual-stream, PoE, metal casing, IP66.

1/2.7" low illumination CMOS sensor

Support H.264/H.265/H.265+ video compression standard, dual-stream
 Max resolution: 3840 × 2160 @20fps

Support precise human shape detection, motor vehicle detection, and custom areas

Support dWDR, backlight compensation, strong light suppression, digital noise reduction and image flipping

Support plugin-free multi-browser access (Chrome, Firefox, Safari, Opera, Edge); Supports the standard ONVIF protocol and can be integrated into numerous large-scale platform management systems both at home and abroad

Support image mask occlusion, protect privacy area

Support OSD Settings and network time calibration

3 pcs Array IR, Max 40 m distance

2.8~12 mm auto focus lens

IP66 metal Turret

support Audio I/O

Power supply: PoE

Camera

Sensor	1/2.7" 8 MP CMOS GC8613
DSP	SSC378DE
Lens	2.8~12 mm
Lighting Mode	dWDR
Active Pixel	3840 x 2160 @20fps
Resolution	8 MP

Image

Video processing	H.264/H.265/H.265+
Compression Code Rate	Support dual-stream; support CBR/VBR code rate <i>Main stream:</i> 20 fps@(3840x2160); 25 fps@(3072x2048); 30 fps@(2592×1944, 2560×1440, 2304×1296) 60 fps@(1920x1080, 1280x720) <i>Sub stream:</i> 720x480, D1, VGA, 640×360
Image Resolution	
Image Settings	AWB, dWDR, BLC, brightness, contrast, strong light suppression, backlight compensation, chromaticity adjustable, etc.
Privacy Mask	Support
Mirror	Support
OSD	Support OSD setting and drag OSD

Intelligent

Motion Detection	Support regional motion detection
Human Detection	Support human shape detection

Network

Audio Processing	G711U/G711A/AAC
Network Interface	One RJ45, 10/100 M adaptive Ethernet port
Protocol support	TCP/IP, HTTP, DHCP, DNS, SMTP, RTMP, RTSP, NTP (HTTPS, SIP, 802.1x, IPv6); ONVIF private
Browser	Preview without plugin support Edge, Chrome, Safari, Firefox, etc.

Interface Function

Audio Input	Linear input
Audio output	Linear output
PoE	Support
Reset	Line control reset button

General

Power Supply	PoE (802.3af)
--------------	---------------

Power Consumption
Operation Temperature
Dimension (DxH)

6 W max
-30 °C ÷ +50 °C; humidity <95% (non-condensing)
133 x 103 mm

