



TWN-24EVR

2 MP HD TVI Bullet Camera, 2.8 ~12 mm varifocal lens, 5 pcs Array LEDs, 40 m IR range, 4-in-1, IP67 metal bullet casing.

High performance CMOS image sensor, with 2.0 mega-pixel resolution
Support common 75-5 similar coaxial cables lossless transmission up to 300 meters above

Max resolution: 1920 x 1080

5 pcs Array LEDs, 40 m IR distance

2.8~12 mm, varifocal lens

default video output TVI, can switch to CVI/AHD/CVBS

support ICR

WDR, 3D-DNR

IP67 metal bullet case

12 Vdc, 500 mA

Camera

Sensor	1/2.9" GC2083
DSP	FH8563H
Number of Pixels	1920 x 1080
Resolution	1080P
Minimum Illumination	0.01 Lux @(F1.2)

Lens

Lens	2.8~12 mm
Lens Type	Varifocal

Camera Features

Video output	TVI/CVI/AHD/CVBS A: 1080p, 720p, 25fps/30fps; C: 1080p, 720p, 25fps/30fps; T: 1080p, 720p, 25fps/30fps; CVBS: 960H 48 dB (min) (AGC closed)
S/N Ratio	48 dB (min) (AGC closed)
OSD	Yes
Day/Night	Ext., B/W, Colour, Auto
White Balance	ATW/MWB
Exposure MODE	GLOBAL/CENTER/BLC/FLC
AWB	GRAY WORLD/ATW/MWB
D-WDR	Close/Open
3D-DNR; 2D-DNR	Auto/Manual (0-10)
CONTRAST; SHARPNESS	Auto/Manual (0-10)
FLIP; MIRROR	Close/Open

General Specification

Language	English, Chinese (Traditional), Italian, Spanish, Russian, French, Polish, Portuguese, Japanese/Korean, E^HN
Transmission distance	75-5, 300 m
Power Input	12 Vdc $\pm$ 1 V
Power Dissipation	50-60 mA
Operation Temperature	-10 °C $\div$ +55 °C; less than 85% RH
Protection	IP67
Dimension (L $\times$ W $\times$ H)	280 $\times$ 84 $\times$ 84 mm

