

# IWN-22IRL

IP BULLET IR



## KEY FEATURES

- Using high performance CMOS image sensor,with 2.0M resolution
- support H.264 ,dual-stream
- Max resolution:1920\*1080
- support Onvif and P2P
- support ICR switching
- 18pcs SMD IR,Max 25M
- 3.6mm lens



SPECIFICATION	IWN-22IRL
Sensor	1/2.8" SONY CMOS
Min Illumination	Color 0.1Lux@F1.2,white/black 0.01 Lux@F1.2
WDR Range	dWDR Range >80dB
Video processing	H.264,dual-stream;CBR/VBR,32K~16M bit/S adjustable;1-25fps adjustable
Main stream	1920*1080,1-25fps 1280*720,1-25fps
Sub stream	720*576,1-25fps ; 640*480,1-25fps 640*352,1-25fps; 320*240,1-25fps
Network Port	1 RJ45 ethernet network port,10M/100M self-adaption
Network protocol	RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP;
IR linkage	support
Operation function	Support WEB setting, OSD,real-time video transmission; motion detection; unified client remote management software, platform system application; complete SDK provided
Standard protocol	Onvif 2.4
Mobile monitor	Support P2P, (IOS, Android)
Power supply	DC10.8V~13.2V, 550mA
Working temperature	-20C~55C
Protection rate	ESD 1kv
IR Distance	Max. 25 meter with 18pcs SMD IR LED
Lens	3.6mm
Camera size	165,2(L) x 66,96 (W) mm x 67,32 (H) mm



## DIMENSIONS:

