

IWN-42IRL

IP BULLET IR




KEY FEATURES

- Using high performance CMOS image sensor,with 4.0M resolution
- support H.264 ,dual-stream
- Max resolution: 2592*1520
- support Onvif and P2P
- support ICR switching
- 18pcs SMD IR,Max 25M
- 3.6mm lens



SPECIFICATION	IWN-42IRL
Sensor	1/3" CMOS
Min Illumination	Color 0.6Lux@F1.2, white/black 0.08Lux@F1.2
Video processing	H264,Baseline/Main Profile/High Profile code,H.265 Main Profile code,MJPEG code,dual-stream,support CBR/VBR code rate,32~16M k bit/S adjustable,1-30fps adjustable
Main stream	2592*1520, 1-15 fps ; 2048*1520,1-25fps(default) 1280*1080,1-25fps ; 1280*720,1-25(30)fps
Sub stream	720*576,1-25fps ; 640*480,1-25fps 640*352,1-25fps ; 320*240,1-25fps
Network Port	1 RJ45 ethernet network port,10M/100M self-adaption
Network protocol	RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP;
IR linkage	support
Operation function	Support WEB setting, OSD,real-time video transmission; motion detection; unified client remote management software, platform system application; complete SDK provided
Standard protocol	Onvif 2.4
Mobile monitor	Support P2P, (IOS, Android)
Power supply	DC10.8V~13.2V, 550mA
Working temperature	-20C~55C
Protection rate	ESD 1kv
IR Distance	Max. 25 meter with 18pcs SMD IR LED
Lens	3.6mm
Camera size	165,2(L) x 66,96 (W) mm x 67,32 (H) mm



DIMENSIONS:

