

TWN-23SMVRB

4 in 1 HD TVI BULLET



KEY FEATURES

- High performance CMOS, 1080P
- Support coaxial transmission for HD video and control signal
- Support common 75-3 similar coaxial cables lossless transmission up to 300 meters
- High speed, long distance, real-time transmission
- ICR, 2D-DNR, dWDR, AGC, AWB
- 5pcs IR Array, 45 meter
- IP66
- 2.8-12mm lens
- TVI (default) / CVI / AHD/ CVBS output



| SPECIFICATION | TWN-23SMVRB |
|-----------------------|-------------------------------------|
| Pick Up Element | 1/2.7"CMOS 2 Mega Pixels |
| Number of Pixels | 1920(H)×1080(V) |
| SYNC. | Internal |
| Resolution | 1080P |
| VIDEO.OUT | AHD/CVI/TVI/CVBS |
| Lens | 2.8-12mm |
| IR Series Distance | Max.45 Meter with 5pcs array IR LED |
| Power supply | DC12V,650mA |
| Minimum Illumination | 0.05Lux(F1.2) |
| Electric Shutter | 1/50s-1/10000s |
| S/N Ratio | 48dB(min)(AGC closed) |
| WDR | dWDR OFF/ON |
| DNR | 2D-DNR |
| WHITE Balance | ATW/MWB |
| AE MODE | GLOBE/BLC |
| OSD | Yes(optional) |
| Coaxial | Yes |
| Day/Night | Ext Color, B/W |
| Transmission distance | 75-5 300M |
| Water Resistance | IP66 |
| Dimension (mm) | 294.5(L)×91.7(W)×92.6(H)mm |
| Storage Temperature | -30~ +60°C RH95% Max |
| Operating Temperature | -20~ +50°C RH95% Max |



DIMENSIONS

