

IMH-22

NETWORK DOME



KEY FEATURES

- Up to 2 megapixel resolution
- Standard video compression with high compression ratio
- Progressive scan CMOS
- PoE (Power over Ethernet)
- Built-in Micro SD/SDHC/SDXC card slot, up to 64 GB
- Dual stream, and the sub-stream for mobile surveillance
- BLC, dWDR, AES, 3D DNR
- 3-axis adjustment for easy installation
- Ingress Protection level: IP66
- Impact Protection: IEC60068-2-75 test, Eh, 20J; EN50102, up to IK10



SPECIFICATION	IMH-22
Camera	
Min. Illumination	0.05Lux @(F1.2,AGC ON)
Shutter Speed	1/25(1/30) s to 1/100,000 s
Lens	4mm@F2.0 (2.8mm optional) Angle of view: 79°(4mm)
Lens Mount	M12
Day &Night	Electronic
Digital Noise Reduction	3D DNR
Angle Adjustment	Pan: ± 15°, Tilt: 0 - 90°, Rotation: ± 15°
WDR	Digital WDR
Compression Standard	
Video Compression	H.264 / MJPEG
H.264 encoding level	Main Profile
Video Bit Rate	32Kbps~16Mbps
Image	
Max. Resolution	1920 x1080
Frame Rate	50Hz: 25fps(1920 x 1080), 25fps (1280 x 960), 25fps (1280 x 720) 60Hz: 30fps(1920 x 1080), 30fps (1280 x 960), 30fps (1280 x 720)
Image Settings	Rotate mode, Saturation, Brightness, Contrast adjustable by client software or web browser
Backlight compensation	Yes, zone optional
ROI	Yes, up to 4 configurable areas
Network	
Network Storage	Local storage: Built-in Micro SD/SDHC/SDXC card slot, up to 64 GB. NAS
Alarm Trigger	Motion detection, Dynamic Analysis, Tampering alarm, Network disconnect, IP address conflict, Storage full, storage error
Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP, RTCP, PPPoE,NTP,UPnP,SMTP,SNMP,IGMP,802.1X,QoS,IPv6, Bonjour
Standard	ONVIF, PSIA, CGI, ISAPI
General function	Flash-prevention, dual stream, reset button, heartbeat, mirror, password protection, video cover, watermark
Interface	
Communication	1 RJ45 10M/100M Ethernet interface
General	
Operating Conditions	-30 °C – 60 °C, Humidity 95% or less (non-condensing)
Power Supply	12 VDC±10% / PoE
Power Consumption	Max. 4W
Protect level	IP66
Impact Protection	IEC60068-275Eh, 20J; EN50102, up to IK10
Dimensions (mm)	99.9 × 97.5 × 46.5 mm
Weight	400g



DIMENSIONS (mm)

